

发光颜料

PHOTOLUMINESCENT PIGMENT



性能指标 Specification

类型 Type	外观颜色 Appearance	发光颜色 Glowing color	型号 Model No.	辉度(mcd/m ²) Luminance at 10min	D50中心粒径(um) Center particle size(D50)
PL系列 PL series	浅黄 Light-yellow	黄绿 Yellow-green	PLO-6B	≥370	50-70
			PLO-6C	≥220	10-30
			PLO-7B	≥450	50-70
			PLO-7C	≥320	15-30
			PLO-7D	≥270	15-25
			PLO-7E	≥170	8-12
			PLO-7F	≥120	5-8
			PLO-8B	≥550	60-85
			PLO-8C	≥400	20-45
	PLO-9C	≥320	15-30		
	浅绿 Light-green	蓝绿 Blue-green	PLB-6B	≥300	50-70
			PLB-6C	≥170	10-30
			PLB-7B	≥380	60-85
			PLB-7C	≥220	10-30
PLB-8B			≥460	60-90	
PLB-8C	≥380	20-45			
黄绿 Yellow-green	黄绿 Yellow-green	PLOY-8C	≥290	10-30	
浅灰 Light-gray	蓝紫 Blue-purple	PLP-6	≥10	20-40	
SP系列 SP series	浅黄 Light-yellow	黄绿 Yellow-green	SP-6	≥300	20-40
	黄绿 Yellow-green	黄绿 Yellow-green	SP-4	≥330	15-35
	浅绿 Light-green	黄绿 Yellow-green	SP-2	≥200	15-25
R系列 R series	鲜红 Red	鲜红 Red	RR-7	≥45(1min)	20-40
	橙红 Orange	橙红 Orange	RO-7	≥95(1min)	20-40
RE系列 RE series	浅白 Light-white	橙红 Orange	REO-1	≥400(1min)	20-40
S系列 S series	浅白 Light-white	天蓝 Blue	SB-8B	≥100	50-70
			SB-8C	≥50	10-30
M系列 M series	红 Red	橙红 Orange	SPMR-4	≥75	20-40
	黄 Yellow	黄 Yellow	SPMY-4	≥150	20-40
	绿 Green	浅绿 Light-green	SPMG-4	≥90	20-40
	蓝 Blue	浅蓝 Light-blue	SPMB-4	≥60	20-40
	橘黄 Orange-yellow	浅橘黄 Light-Orange	SPMRY-5	≥170	30-50
	黄 Yellow	黄绿 Yellow-green	SPMY-5	≥200	30-50



大连路明发光科技股份有限公司
DALIAN LUMINGLIGHT CO., LTD.

地址: 中国·大连市高新园区高能街32号 电话: 0411-84798528 网址: www.luminglight.cn
Add: No. 32, Gaoneng Str, High-Tech zone, Dalian, China Tel: 0411-84798528